


# VSH SERIES SHORT HEIGHT JACK



## FEATURES / APPLICATION

- Single Acting Spring Return Upto 200 Tons.
- Best used for applications with low clearance.
- Compatible with all reputed brands pumping units.
- Heavy equipment lifting & alignment.
- Used in horizontal & vertical directions.
- Ideally ensure no gap between jack & load to be lifted, to utilize full stroke
- Provided with In-Built Hardened saddle to avoid ram mushrooming
- Refer to anatomy for all VANKOS-HYD jacks.

## CAPACITY 10 - 200 TON | STROKE 30 - 60 MM | MAX. WORKING PRESSURE 700 BAR

Rated Capacity (Ton)	Capacity @700 bar (KN)	Stroke (mm)	Model	Effective Area (cm <sup>2</sup> )	Oil cap (cc)	A Closed Height (mm)	B Cylinder OD (mm)	C Bore Dia (mm)	D Ram Dia (mm)	W A/F (mm)	Wt (Approx.) (kg)
10	111	30	RC-VSH-10/30	15.9	48	90	70	45	35	-	2.3
20	218	50	RC-VSH-20/50	31.2	160	115	90	63	50	-	4.9
30	309	50	RC-VSH-30/50	44.2	221	120	100	75	60	-	6
50	550	60	RC-VSH-50/60	78.5	471	125	130	100	80	60	11
75	792	60	RC-VSH-75/60	113.1	679	145	155	120	95	70	18.4
100	1077	60	RC-VSH-100/60	153.9	925	150	180	140	110	80	23.6
150	1589	60	RC-VSH-150/60	227.0	1362	165	220	170	140	100	43
200	2199	60	RC-VSH-200/60	314.2	1885	200	255	200	160	110	66

- Higher capacity and customized solutions on request.
- Specifications are subject to change due to continual improvement.
- Capacity and Stroke specified are maximum safe limits.
- Use at 80% of rating as safe practice.

### SELECT SUITABLE PUMPING UNITS AND ACESORIES



## Vankos & Company (Hyderabad)

Plot No. 457 & 458, S.V.C.I.E, IDA, Phase-I, Jeedimetla, Hyderabad-500055

sales@vankoshyd.com | www.vankoshyd.com